

## LNE-SM-G 软管接头

### UNION FOR FLEXIBLE PIPES

产品材质: PA尼龙 (polyamide)

螺纹规格: 公制螺纹 (Metric) / 德制螺纹 (PG) / 英制螺纹 (G)

工作温度: -40°C ~ +110°C

颜色: 黑色, 其它颜色可以订做

特性: 内锁扣和本体特殊设计, 装卸只需拔插无需工具

使用方法: LNE-SM-G型软管接头是软管的配套产品, 可接入设备箱体上, 也可以根据选用螺纹接入进出口为内螺纹的电动设备上, 只需软管插入接口即可

Product material: PA (polyamide)


Specification of thread: Metric/PG/G thread

Working temperature: -40°C ~ +110°C

Color: Black. Other colors are customizable

Property: Special design with inner locking buckle making the mounting and dismounting done by simple plugging or pulling, without using tools.

How to use: LNE-SM-G type flexible pipe joints are the fittings of the flexible pipes, which can be either connected with the housing of equipments or connected with electric equipment with inner threaded access hole as per the thread selected. Simply insert the flexible pipe into the union.



## RoHS

型号 Item No.	软管规格 Specification for flexible pipe	螺纹尺寸公制 Metric dimension of thread	AG外径(mm) AG Outer diameter	AG内径(mm) AG Inner diameter	GL(mm)	H	包装单位个包 Packaging unit: Unit/bag
LNE-SM-G-M12	AD10.0	M12×1.5	12.0	6.5	10.0	22.5	100
LNE-SM-G-M12	AD13.0	M12×1.5	12.0	8.0	10.0	26.0	100
LNE-SM-G-M16	AD13.0	M16×1.5	16.0	10.0	10.0	23.0	100
LNE-SM-G-M18	AD13.0	M18×1.5	18.0	10.0	11.5	23.0	100
LNE-SM-G-M20	AD13.0	M20×1.5	20.0	10.0	11.5	23.0	100
LNE-SM-G-M18	AD15.8	M16×1.5	18.0	12.0	10.0	24.0	100
LNE-SM-G-M16	AD15.8	M18×1.5	18.0	12.0	11.5	24.0	100
LNE-SM-G-M20	AD15.8	M20×1.5	20.0	12.0	11.5	24.0	100
LNE-SM-G-M20	AD18.5	M20×1.5	20.0	14.3	12.0	25.5	50
LNE-SM-G-M20	AD21.2	M20×1.5	20.0	17.0	13.0	27.0	50
LNE-SM-G-M24	AD21.2	M24×1.5	24.0	17.0	13.0	27.0	50
LNE-SM-G-M25	AD21.2	M25×1.5	25.0	17.0	13.0	27.0	50
LNE-SM-G-M25	AD25.0	M25×1.5	25.0	20.0	14.0	30.0	50
LNE-SM-G-M25	AD28.5	M25×1.5	25.0	23.0	20.0	34.0	50
LNE-SM-G-M27	AD28.5	M27×2.0	27.0	23.0	14.0	34.0	50
LNE-SM-G-M30	AD28.5	M30×2.0	30.0	22.0	11.0	33.0	50
LNE-SM-G-M32	AD28.5	M32×1.5	32.0	25.0	14.0	33.0	50
LNE-SM-G-M32	AD34.5	M32×1.5	32.0	29.0	20.0	36.0	20
LNE-SM-G-M36	AD34.5	M36×2.0	36.0	29.0	14.0	36.0	20
LNE-SM-G-M40	AD34.5	M40×1.5	40.0	29.0	15.0	38.5	20
LNE-SM-G-M40	AD42.5	M40×1.5	40.0	36.0	15.0	38.5	10
LNE-SM-G-M48	AD42.5	M48×2.0	48.0	36.0	15.0	38.5	10
LNE-SM-G-M50	AD54.5	M50×1.5	50.0	38.0	16.0	39.0	10
LNE-SM-G-M60	AD54.5	M60×2.0	60.0	53.0	16.0	39.0	10
LNE-SM-G-M63	AD54.5	M63×1.5	63.0	53.0	16.0	39.0	10

型号 Item No.	软管规格 Specification for flexible pipe	螺纹尺寸德制 Dimension of thread	AG外径(mm) AG Outer diameter	AG内径(mm) AG Inner diameter	GL(mm)	H
LNE-SM-G-PG7	AD10.0	PG7	12.3	6.5	11.5	18.0
LNE-SM-G-PG9	AD13.0	PG9	15.0	10.0	11.5	19.0
LNE-SM-G-PG11	AD15.8	PG11	18.4	12.0	12.0	23.0
LNE-SM-G-PG13.5	AD15.8	PG13.5	20.2	14.3	12.0	25.0
LNE-SM-G-PG13.5	AD18.5	PG13.5	20.2	14.3	12.0	25.0
LNE-SM-G-PG16	AD21.2	PG16	22.3	17.0	13.0	27.0
LNE-SM-G-PG21	AD28.5	PG21	28.0	23.0	13.0	33.0
LNE-SM-G-PG29	AD34.5	PG29	36.7	29.0	15.0	35.0
LNE-SM-G-PG36	AD42.5	PG36	46.7	36.0	15.0	38.5
LNE-SM-G-PG48	AD54.5	PG48	59.0	53.0	16.0	39.0

型号 Item No.	软管规格 Specification for flexible pipe	螺纹尺寸英制 G dimension of thread	AG外径(mm) AG Outer diameter	AG内径(mm) AG Inner diameter	GL(mm)	H
LNE-SM-G1/2	AD21.2	G1/2	20.9	17.0	13.0	27.0
LNE-SM-G1/2	AD25.0	G1/2	20.9	20.0	14.0	30.0
LNE-SM-G3/4	AD28.5	G3/4	26.0	23.0	14.0	34.0
LNE-SM-G1"	AD34.5	G1"	33.0	29.0	14.0	36.0